





If lift is damaged or malfunctioning: Do Not Operate! ©

The sketch is same to the information words, aslo has mostly described the accidents all kinds of lifts maybe occur.

TAICANG CHENGMING HYDRAULICS CO.,LTD

No.90 NORTH CHENGXI RD.,CHENGXIANG TOWN,TAICANG CITY,JIANGSU,CHINA

Model: SHE40 Serial Nr.: 20140111
Capacity: 4000 Kg Lifting Height: 1900 mm
Voltage: 380 V Power: 2.2 K.W
Weight: 680 Kg
Production date: 20140111



Produced for UAB "Amanda"
Gedimino Av. 2/1-24, Vilnius LT-01103, Lithuania
E-mail: info@amanda.lt, www.amanda.lt



4000KG

120540383

WARNING Stay clear of area if vehicle is in danger of falling.	WARNING The vehicle's center of gravity should always be midway between the center points.
WARNING Keep away from the lift while raising and lowering it.	WARNING Avoid large weaving when the vehicle is raising and lowering.
WARNING	WARNING



Operation

1. Switch on power supply power supply indicator on
2. Push 'Up' button, interlocks locking together, electric motor get electricity then start running. When on the working platform being raised up. When release the button, raise being stopped.
3. Push 'Lock' button, releases on the working platform will be locked at a maintenance lock.
4. Push 'Down' button, under power release section of the motor, the motor being stopped. Mechanical lock being opened at the same time, all motor electromagnetic release being opened when gets electricity, then begin to fall. Release button, then push 'Lock' button when don't need fall.
5. In case of an emergency directly push the emergency stop button, after the problem being solved, rotate the button clockwise to '0' is needed.

ATTENTION: When repair vehicles, the operator must being aware of mechanical lock and safety of power supply, to avoid misoperation and accidents.

IP54 CE



CARGO

CARGO LIFT

www.bads.it



Manufacturer's specific vehicle lifting points. Some vehicles
have a label inside the right front door lock face or are
marked with angle shape marks on the vehicle's undercarriage.

load and to the extent that, after
raising a short distance, the
vehicle shall be checked to
ensure that it is correctly and
safely positioned.

Model:	LF-140BPE	Serial No:	E10081751
Lift capacity:	4000 Kg	Lift height:	1800 mm
Power supply:	220 V	Power of motor:	2200 W
Machine weight:	600 kg	Date:	2010.08.23